

PROFORCE[®] UST

2003 PRODUCT GUIDE

Proforce[®] XL Ultra Light - New for 2003

The latest ultra light design utilizes Proforce Tip Technology for optimum performance in today's larger heads.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
6000L	56g	4.5	Low	4.0"	.335"	.580"	45"
6000A	58g	4.0	Low-Mid	4.0"	.335"	.595"	46"
6000R	61g	3.9	Mid	4.0"	.335"	.600"	46"
6000S	61g	3.9	Mid-High	4.0"	.335"	.600"	46"
6000X	64g	3.9	High	4.0"	.335"	.605"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

This new Ultra Light shaft was specifically designed for performance. If you expect to win, play the latest technology. Older designs just don't measure up. The flex point was designed for each flex to optimize ball flight.

The Proforce XL comes in a White Pearl finish with a Gold & Purple logo and is available for parallel tip woods in .335 tip diameter only.

Proforce[®] ATR

Accelerated Tip Response (ATR) design adds unique performance to Proforce shafts.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
3930L	71g	4.0	Low	4"	.335"	.590"	45"
3930A	72g	3.5	Low	4"	.335"	.590"	46"
3930R	73g	3.5	Mid	4"	.335"	.610"	46"
3930S	76g	3.4	Mid	4"	.335"	.615"	46"
3930X	79g	3.4	Mid-High	4"	.350"	.620"	46"
3936L	72g	4.0	Low	3.5"	.350"	.590"	45"
3936A	73g	3.5	Low	4"	.350"	.590"	46"
3936R	74g	3.5	Mid	4"	.350"	.610"	46"
3936S	78g	3.4	Mid	4"	.350"	.615"	46"
3936X	81g	3.4	Mid-High	4"	.350"	.620"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

A modified, second generation, "Proforce Technology" design for golfers who desire a higher launch angle. Purposely engineered with a more responsive tip section, resulting in a steeper launch angle and longer carry distance. Weight, torque and tip flexibility have all been optimized to create the perfect golf shaft for players wanting longer ball flight.

Available in our standard Proforce Yellow Gold shaft color with a racy new Red logo. Proforce ATR's are offered in parallel tip woods in .335 tip and .350 tip diameters.

Proforce[®] PUREGOLD™ - New for 2003

Feel the difference.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
6000L	56g	4.5	Low	4"	.335"	.580"	45"
6000A	58g	4.0	Low-Mid	4"	.335"	.595"	46"
6000R	61g	3.9	Mid	4"	.335"	.600"	46"
6000S	61g	3.9	Mid-High	4"	.335"	.600"	46"
6000X	64g	3.9	High	4"	.335"	.605"	46"

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
3930L	71g	4.0	Low	4"	.335"	.590"	45"
3930A	72g	3.5	Low	4"	.335"	.590"	46"
3930R	73g	3.5	Mid	4"	.335"	.610"	46"
3930S	76g	3.4	Mid	4"	.335"	.615"	46"
3930X	79g	3.4	Mid-High	4"	.335"	.620"	46"

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
5355A	61g	4.4	Mid	3.5"	.335"	.600"	46"
5355R	63g	4.3	Mid	3.5"	.335"	.605"	46"
5355S	63g	4.3	Mid	3.5"	.335"	.605"	46"

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7850A	69g	3.4	Mid-High	4"	.335"	.605"	46"
7850R	71g	3.4	Mid-High	4"	.335"	.610"	46"
7850S	71g	3.4	Mid-High	4"	.335"	.610"	46"
7850X	74g	3.4	Mid-High	4"	.335"	.615"	46"

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7550R	77g	3.3	High	4"	.335"	.615"	46"
7550S	81g	3.3	High	4"	.335"	.618"	46"
7550X	81g	3.3	High	4"	.335"	.618"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

UST now offers Proforce PUREGOLD™ shafts as an upgrade opportunity. The SST PURE® process identifies a shaft's most stable alignment position. Shafts are PUREd® prior to painting and graphics application so that logos are properly positioned at address and in perfect alignment for easy assembly.

You can feel the difference by installing a PUREGOLD™ Proforce shaft in your clubhead. Just as new tires must be balanced for maximum performance on your car, your club's performance can be maximized by proper shaft orientation. The SST PURE® process identifies a shaft's most stable alignment position.

Optimize your club's performance by choosing the PUREGOLD™ shaft option.

Available now in .335" tip Proforce 55, 65, 75, ATR, and the all new Proforce XL Ultra Light.

SST PUREd® is the USGA approved process of shaft spine orientation. The technology is licensed to UST by Strategic Shaft Technologies, holder of U.S. Patent #4,958,834 and other patents pending. SST Pure® and SST PUREd® are registered trademarks of Strategic Shaft Technologies, L.P.

PROFORCE® TOUR SERIES

Proforce® 85 Gold - New lower pricing for 2003

Tour proven mid-weight design produces optimum launch angles and proper spin rates.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7885R	85g	3.0	High	4"	.335"	.605"	46"
7885S	88g	3.0	High	4"	.335"	.610"	46"
7885X	89g	3.0	High	4"	.335"	.610"	46"
7886R	86g	3.0	High	4"	.350"	.605"	46"
7886S	89g	3.0	High	4"	.350"	.610"	46"
7886X	90g	3.0	High	4"	.350"	.610"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

This Tour design utilizes highest quality carbon fibers to produce an optimum blend of flex, more weight, lower torque and Proforce Technology. Provides more control for the golfer looking for a heftier feel. Popular among Top amateurs and College players. Designed for Driver and Fairway Wood installation.

Comes in our Proforce Yellow Gold with a racy Purple logo with red accents. Offered in parallel tip woods in .335 and .350 tip diameters.

Proforce® 95 Gold - New lower pricing for 2003

Tour weight Proforce design provides a solid feel at impact.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7895R	97g	2.0	High	4"	.335"	.610"	46"
7895S	98g	2.0	High	4"	.335"	.610"	46"
7895X	100g	2.0	High	4"	.335"	.610"	46"
7896S	99g	2.0	High	4"	.350"	.610"	46"
7896X	101g	2.0	High	4"	.350"	.610"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

This Tour Design is the heaviest Proforce offering. Designed with the highest quality carbon fibers and possessing very low torque, high flex point and superb tip stability. Delivers tremendous driving distance with a premium on accuracy. Designed for Driver and Fairway Wood installation.

In our Proforce Yellow Gold with a racy Purple logo with Red accents. Offered in parallel tip woods in .335 tip and .350 tip diameters.

Proforce® I.T. Gold - New lower pricing for 2003

Counter balanced Tour weight design, a Tour proven winner.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
5190R	91g	3.5	Mid	3.5"	.335"	.600"	45"
5190S	94g	3.1	Mid	3.5"	.335"	.600"	45"
5190X	97g	3.1	Mid	3.5"	.335"	.605"	45"
5196R	92g	3.5	Mid	3.5"	.350"	.600"	45"
5196S	95g	3.1	Mid	3.5"	.350"	.600"	45"
5196X	98g	3.1	Mid	3.5"	.350"	.605"	45"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

This proven Tour design accomplishes impressive gains in distance by redistributing weight to the butt section of the club. This weight counter balancing allows the golfer to generate more club head speed with less effort and takes advantage of momentum by allowing more mass to be used in the club head.

Comes in our Proforce Yellow Gold with a racy Purple logo with Red accents. Offered in parallel tip woods in .335 and .350 tip diameters.

PROFORCE® SPECIALTY SERIES

Proforce® Fairway Gold

Designed especially for fairway woods with Proforce Tip Technology.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7950R	82g	2.8	Mid	3.5"	.335"	.610"	44"
7950S	84g	2.8	Mid	3.5"	.335"	.610"	44"
7950X	86g	2.8	Mid	3.5"	.335"	.610"	44"
7960R	83g	2.8	Mid	3.5"	.350"	.610"	44"
7960S	86g	2.8	Mid	3.5"	.350"	.610"	44"
7960X	87g	2.8	Mid	3.5"	.350"	.610"	44"

Trimming instructions – N/A for Driver, 0" for 3W, 1" for 5W and 2" for 7W.

Optimum weight, shaft flex, low torque and Proforce Tip Technology provides the ultimate fairway wood performance. Designed as a transition weighted fairway wood shaft. For the golfer that uses a lightweight driver and wants a heavier feel in his fairway woods. Mid flex design aids player in getting the ball airborne from the Fairway.

Comes in our Proforce Yellow Gold with a racy Purple logo. Offered in parallel tip woods in .335 tip and .350 tip diameters.

Proforce® LD Gold - Long Drive

Proforce Tip Technology provides the tip stability needed for Long Drive Competitions.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7850S	78g	3.3	Mid-High	4"	.335"	.610"	50"
7850X	81g	3.3	Mid-High	4"	.335"	.620"	50"
7850XX	84g	3.3	Mid-High	4"	.335"	.620"	50"
7850XX	86g	3.3	Mid-High	4"	.335"	.620"	50"
7860S	79g	3.2	Mid-High	4"	.350"	.610"	50"
7860X	82g	3.2	Mid-High	4"	.350"	.620"	50"
7860XX	85g	3.2	Mid-High	4"	.350"	.620"	50"
7860XXX	87g	3.2	Mid-High	4"	.350"	.620"	50"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

Based on the design of the Proforce 65 with a purchase length of 50 inches. Designed for the golfer who wants to build that extra long driver with Proforce accuracy. Tip stiff for distance with that long boring ball flight.

Engineered for Driver installation only. Comes in our Proforce Yellow Gold with a racy Purple logo. Offered in parallel tip woods in .335 and .350 tip diameters.

PROFORCE® IRON SHAFTS

Proforce® 75 Gold Tour Iron Shaft

A high performance lightweight iron shaft designed with Proforce Tip Technology.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
642A	79g	3.3	Mid	5.5"	.370"	.595"	40"
642R	81g	3.2	Mid	5.5"	.370"	.595"	40"
642S	83g	3.2	Mid	5.5"	.370"	.600"	40"
642X	83g	3.2	Mid	5.5"	.370"	.600"	40"
675TA	80g	2.8-3.1	Mid	Taper	.355"	.605"	35.5-40"
675TR	81g	2.8-3.1	Mid	Taper	.355"	.600"	35.5-40"
675TS	81g	2.7-3.0	Mid	Taper	.355"	.610"	35.5-40"
675TX	81g	2.6-2.9	Mid	Taper	.335"	.610"	35.5-40"

Trimming instructions for parallel tip irons only:

0" for 1i, .5" for 2i, 1" for 3i, 1.5" for 4i, 2" for 5i, 2.5" for 6i, 3" for 7i, 3.5" for 8i and 4" for 9i, PW and SW.

The first iron shaft worthy of the Proforce colors. The Proforce 75 Gold provides the ultimate in iron shaft performance – consistency, accuracy and distance. High performance materials and quality shaft design allow the golfer to control ball flight like never before.

The taper tip models are constant weight for a more consistent set. Constant weight shafts help with trajectory. Short irons have higher flex points for ball control and the long irons have a lower flex point for higher ball flight. Available in parallel tip and incremental length, constant weight taper tip iron shafts.

Proforce® 95 Gold Iron Shaft

Step Winding Technology

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
410R	91-98g	1.8-2.4	High	2"	.370"	.600"	35-39"
410S	93-99g	1.8-2.3	High	2"	.370"	.600"	35-39"
410TR	91-97g	1.8-2.4	High	Taper	.355"	.600"	35-39"
410TS	93-99g	1.8-2.3	High	Taper	.355"	.600"	35-39"
410TX	91-99g	1.8-2.4	High	Taper	.355"	.600"	35-39"

These shafts are butt trim only because they are incremental length irons shafts.

A look that is very different than any other shaft. The Step Winding Technology (patent pending) give the Proforce 95 stability and performance like no other. Higher ball flight in the long irons and tighter shot dispersion in the short irons. No need to adjust club length or swing weight when switching from steel.

The 95 gold is finished in a clear Graphite Black with Yellow Gold and White logo. Available in incremental length parallel tip and tapered tip iron shafts.

Proforce® Tour Weight Iron Shaft

Tour Proven Winner with Proforce Tip Technology.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
450R	110g	2.6	High	5.5"	.370"	.600"	40"
450S	113g	2.6	High	5.5"	.370"	.600"	40"
450X	114g	2.6	High	5.5"	.370"	.600"	40"
450TR	102-112	1.8-2.6	High	Taper	.355"	.600"	35.5-40"
450TS	100-115	1.8-2.6	High	Taper	.355"	.600"	35.5-40"
450TX	103-115	1.8-2.6	High	Taper	.355"	.600"	35.5-40"

Trimming instructions for parallel tip irons only:

0" for 1i, .5" for 2i, 1" for 3i, 1.5" for 4i, 2" for 5i, 2.5" for 6i, 3" for 7i, 3.5" for 8i and 4" for 9i, PW and SW.

Low Torque and High Flex Point provide the standard for better players looking to switch from steel to graphite. A real benefit of graphite iron shafts for golfers is shock absorption. Less wear and tear on the hands, elbows and shoulders. Weight and balance Tour Players prefer.

Available in parallel tip and incremental length, tapered tip iron shafts.

NOTE: All taper tip iron shaft models are constant weight for a more consistent set of shafts. Constant weight shafts help with trajectory. Short irons will give you a higher flex point for better ball control. And long irons have a lower flex point to give you a higher ball flight.

PROFORCE® LADY SERIES

Proforce® 65 Lady - woods and iron

Woods and Irons engineered with Proforce Technology to fit the Lady Golfers of today.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7850L-CB	67g	3.6	Low	4"	.335"	.580"	44"
7850L-EB	66g	3.6	Low	4"	.335"	.580"	44"
785L-CB	66g	4.8	Low	4.75"	.370"	.570"	39"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

0" for 3i, .5" for 4i, 1" for 5i, 1.5" for 6i, 2" for 7i, 2.5" for 8i and 3" for 9i, PW and SW.

Lightweight graphite with a low flex point. Engineered from the start with women golfers in mind wanting the great playing characteristics of a Proforce.

Available in Champagne Bronze in woods and irons and as a second option in Electric Blue in the woods only. Only offered in parallel tip woods and irons.

STANDARD PROFORCE® MODELS

Proforce® 55 Gold - Tour Proven

The classic light weight Proforce.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
5355A	61g	4.4	Mid	3.5"	.335"	.600"	46"
5355R	63g	4.3	Mid	3.5"	.335"	.605"	46"
5355S	63g	4.3	Mid	3.5"	.335"	.605"	46"
5356A	62g	4.4	Mid	3.5"	.350"	.600"	46"
5356R	64g	4.3	Mid	3.5"	.350"	.605"	46"
5356S	64g	4.3	Mid	3.5"	.350"	.605"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

This ultra light is equipped with Proforce Tip Technology and was engineered to produce a slightly higher ball flight to maximize distance. A mid flex point and softer tip section produce slightly higher launch angles for maximum ball carry.

The Proforce 55 makes an excellent driver shaft and comes in our standard Proforce Yellow Gold with a racy Purple logo. Offered in parallel tip woods in .335 tip and .350 tip diameters.

Proforce® 65 Gold - Tour Proven

The original tip stiff Proforce.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7850A	69g	3.4	Mid-High	4"	.335"	.605"	46"
7850R	71g	3.4	Mid-High	4"	.335"	.610"	46"
7850S	71g	3.4	Mid-High	4"	.335"	.610"	46"
7850X	74g	3.4	Mid-High	4"	.335"	.615"	46"
7860R	72g	3.3	Mid-High	4"	.350"	.610"	46"
7860S	72g	3.3	Mid-High	4"	.350"	.610"	46"
7860X	74g	3.3	Mid-High	4"	.350"	.615"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

This Proforce tip stiff shaft has it all - built for distance and accuracy off the tee with very light weight yet low torque for tight shot dispersion that is Tour proven. An excellent lightweight shaft for the strong player. The Proforce 65 is constructed with some of the most advanced high modulus fibers available.

This shaft works well in driver and fairway wood installations and is offered in parallel tip woods with either .335" tip or .350" tip diameters. Finished in our standard Proforce Yellow Gold and Purple colors.

Proforce® 75 Gold - Tour Proven

Proforce Tip Technology and high flex point, for control and a low, penetrating ball flight.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
7550R	77g	3.3	High	4"	.335"	.615"	46"
7550S	81g	3.3	High	4"	.335"	.618"	46"
7550X	81g	3.3	High	4"	.335"	.618"	46"
7560R	78g	3.2	High	4"	.350"	.615"	46"
7560S	82g	3.2	High	4"	.350"	.618"	46"
7560X	82g	3.2	High	4"	.350"	.618"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

Proforce tip technology originated with the Proforce 75, a "beefed up" light weight shaft with low torque and very high kick point. The lower torque keeps the shot pattern tighter on miss-hits, while the tip stiff design creates a low, boring ball flight. Our most popular Proforce model on Tour.

Designed for driver and fairway woods and finished in our standard Proforce Yellow Gold and Purple. Offered in parallel tip woods with either .335" tip or .350" tip diameters.

MASP PROGRAM – 2003 "Minimum Advertised Selling Price"

Beginning January 1, 2003, UST will implement a new MASP (Minimum Advertised Selling Price) program. MASP includes any and all published, printed, electronic or mailed price lists. This program is necessary to protect the valuable, high quality brand image of UST golf shafts. We reserve the right to discontinue sales to any reseller who advertises any UST shafts below the MASP. Please see the 2003 Confidential Price List showing the "MASP" for each model. We trust that you understand the significance of protecting the UST brand and appreciate your cooperation in following the MASP.

ORDERING INFORMATION

- To order within the continental U.S., contact our Customer Service Department at 1-800-621-6728 or e-mail us at: info@ustgolfshaft.com
- Our hours are Monday through Thursday from 7:30am until 5:00pm CST and Fridays from 7:30am until 2:30pm CST.
- If ordering from outside the USA, please call (817) 267-2219, fax UST at (817) 283-1722 or e-mail us at info@ustgolfshaft.com.
- Minimum order quantities apply to all purchases.

RETURNS

- Please notify UST of any discrepancy within 10 days after receipt of your order.
- Returns will not be accepted without a Return Authorization number from UST.
- Returns of non-defective merchandise are subject to a 15% restocking charge.

2003 PRODUCT GUIDE



ACCRA™ 65 and ACCRA™ 75 - The Ultimate in Shaft Performance! Tour proven.

Proforce Technology taken to the highest level with launch control.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
8065R	70g	2.4	Mid	3.5"	.335"	.600"	46"
8065S	72g	2.4	Mid	3.5"	.335"	.600"	46"
8065X	74g	2.4	Mid	3.5"	.335"	.605"	46"
8066R	70g	2.4	Mid	3.5"	.350"	.600"	46"
8066S	72g	2.4	Mid	3.5"	.350"	.600"	46"
8066X	74g	2.4	Mid	3.5"	.350"	.605"	46"
MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
8075R	80g	2.0	Mid	3.5"	.335"	.600"	46"
8075S	80g	2.0	Mid	3.5"	.335"	.600"	46"
8075X	83g	2.0	Mid	3.5"	.335"	.605"	46"
8076R	81g	2.0	Mid	3.5"	.350"	.600"	46"
8076S	81g	2.0	Mid	3.5"	.350"	.600"	46"
8076X	84g	2.0	Mid	3.5"	.350"	.605"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

UST has pushed the limits in leading edge, advanced technology golf shaft designs. By utilizing the latest, ultra high modulus, aerospace quality carbon fiber materials along with Tour proven "Proforce Tip Technology" formulas, UST design engineers have created THE premium performance golf shaft.

Launch conditions are optimized with the new ACCRA 65 and ACCRA 75 shaft series because of this bold new merger of materials and design technology. The ACCRA series established new standards by which all other, so called, "premium shafts" are measured.

ACCRA is the performance upgrade shaft for you. Incredibly low torque, a perfectly balanced flex point, and tip stiffness combine to create optimum ball speed, spin rate and launch trajectory.

Finished in Pearl Silver Frost, with metallic smoky gray graphics and available in .335" tip and .350" tip designs.

Super 47 Lite

Super Ultra Light built for driving distance and accuracy.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
5450A	50g	4.9	Mid	3.5"	.335"	.600"	46"
5450R	50g	4.7	Mid	3.5"	.335"	.600"	46"
5450S	54g	4.7	Mid	3.5"	.335"	.605"	46"
5455R	52g	4.7	Mid	3.5"	.350"	.600"	46"
5455S	54g	4.7	Mid	3.5"	.350"	.605"	46"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

An excellent ultra light driver shaft built for distance and accuracy off the tee. The Super 47 is constructed with the most advanced graphite fibers resulting in torque that's lower than most shafts that weigh nearly twice as much. Added strength and tip stability are achieved by using the new high impact resistant fiber, Zylon™.

The Super 47 is finished Silver and Black two tone graphics and is available in .335" and .350" parallel tip woods only.

2003 PRODUCT GUIDE

Competition 75 Series™ Combination Flex Shafts

The new Performance/Value standard.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
6300A/L	80g	5.8	Low	4.5"	.335"	.590"	47"
6300R/S	86g	5.5	Mid	4.5"	.335"	.600"	47"
630A/L	80g	4.8	Low	6.5"	.370"	.590"	42"
630R/S	83g	4.6	Mid	6.5"	.370"	.600"	42"

Trimming instructions – 1" for Driver, 2" for 3W and 3" for 5W & 7W.

Trimming instructions for irons:

0" for 1i, .5" for 2i, 1" for 3i, 1.5" for 4i, 2" for 5i, 2.5" for 6i, 3" for 7i, 3.5" for 8i and 4" for 9i, PW and SW.

With an extremely rugged yet light weight design, and a long parallel tip section the combo flex Competition 75 Series of shafts offers an unprecedented level of club building flexibility.

Available in attractive Proforce style two tone graphics – Midnight Blue and Silver for the mid kick, firm flex R/S and bright Blue and Silver for the low kick, lite flex A/L's. These shafts are also ideal for low hosel and no hosel designed club heads.

Available in parallel tip woods and irons.

Speed Rated™ Series

High Performance, Easy-to-Fit Shaft System based on swing speed.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
SR6	63g	5.0	Low	3.5"	.335"	.600"	46"
SR6-I	70g	5.0	Low	5.5"	.370"	.565"	39"
SR7	65g	4.9	Low	3.5"	.335"	.610"	46"
SR7-I	75g	4.6	Low	5.5"	.370"	.590"	40"
SR8	68g	4.6	Mid	3.5"	.335"	.615"	46"
SR8-I	84g	3.4	Mid	5.5"	.370"	.595"	40"
SR9	72g	4.6	Mid	3.5"	.335"	.618"	46"
SR9-I	85g	3.3	High	5.5"	.370"	.600"	40"
SR10	73g	4.6	Mid	3.5"	.335"	.618"	46"
SR10-I	90g	2.4	High	5.5"	.370"	.600"	40"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

Trimming instructions for irons:

0" for 1i, .5" for 2i, 1" for 3i, 1.5" for 4i, 2" for 5i, 2.5" for 6i, 3" for 7i, 3.5" for 8i and 4" for 9i, PW and SW.

UST's SR Speed Rated family of shafts uses swing speed as the basis for this complete shaft fitting system. The flex of each shaft has been chosen to fit the golfer's driver swing speed and/or 5-iron carry distance:

SR6 = swing speeds of 60+ mph
SR6-I = 5 iron carry of 100+ yards

SR7 = swing speeds of 70+ mph
SR7-I = 5 iron carry of 130+ yards

SR8 = swing speeds of 80+ mph
SR8-I = 5 iron carry of 150+ yards

SR9 = swing speeds of 90+ mph
SR9-I = 5 iron carry of 170+ yards

SR10 = swing speeds of 100+ mph
SR10-I = 5 iron carry of 190+ yards

Flex points range from high in the stronger flexes to low in the softer flexes. A lightweight design is used in the wood shafts and lightweight to medium weight designs are used in the iron shafts.

Mens' SR Series shafts are finished in a matte black with a White and Gold logo. The ladies Speed Rated shafts are finished in a Soft Champagne with a White and Copper logo.

Competition Series™ PRO

A lightweight, durable replacement shaft.

MODEL	WEIGHT	TORQUE	FLEX PT.	TIP PARALLEL	TIP OD	BUTT OD	LENGTH
3500L	74g	5.4	Low	3.5"	.335"	.565"	45"
3500A	76g	5.2	Low	3.5"	.335"	.590"	45"
3500R	78g	4.9	Mid	3.5"	.335"	.595"	45"
3500S	81g	4.9	Mid	3.5"	.335"	.600"	45"
350L	70g	5.0	Low	5.5"	.370"	.565"	40"
350A	75g	4.6	Low	5.5"	.370"	.590"	40"
350R	75g	4.3	Mid	5.5"	.370"	.595"	40"
350S	78g	4.3	Mid	5.5"	.370"	.600"	40"

Trimming instructions – 0" for Driver, 1" for 3W and 2" for 5W & 7W.

Trimming instructions for irons:

0" for 1i, .5" for 2i, 1" for 3i, 1.5" for 4i, 2" for 5i, 2.5" for 6i, 3" for 7i, 3.5" for 8i and 4" for 9i, PW and SW.

The standard length 3500/350 model shafts are offered in ladies, senior, regular and stiff flexes. A highly durable yet lightweight shaft with medium torque the Competition Series PRO lineup is a proven value and performance leader.

All shafts are finished in a neutral Pearl Gray finish with Gold and Black logos. Available in parallel tip wood and iron shaft models only.