

2006 Product Guide

NEW Proforce V2: Super low-torque technology is taking the Tour by storm!



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
5050	A	56g	3.7°	High	.600"	237	5.6	23	4.0"	.335"	46"
5050	R	57g	3.7°	High	.600"	252	6.3	26	4.0"	.335"	46"
5050	S	57g	3.7°	High	.600"	269	7.1	28	4.0"	.335"	46"
5050	X	59g	3.6°	High	.600"	284	7.9	29	4.0"	.335"	46"
5056	A	57g	3.6°	High	.600"	237	5.6	23	4.0"	.350"	46"
5056	R	58g	3.6°	High	.600"	252	6.3	26	4.0"	.350"	46"
5056	S	58g	3.6°	High	.600"	269	7.0	28	4.0"	.350"	46"
5056	X	60g	3.5°	High	.600"	284	7.9	29	4.0"	.350"	46"
6060	A	63g	3.1°	Med	.600"	239	5.7	24	4.0"	.335"	46"
6060	R	65g	3.0°	Med	.600"	252	6.3	26	4.0"	.335"	46"
6060	S	66g	3.0°	Med	.600"	267	7.0	28	4.0"	.335"	46"
6060	X	66g	2.9°	Med	.600"	282	7.8	30	4.0"	.335"	46"
6066	R	66g	2.9°	Med	.600"	252	6.3	26	4.0"	.350"	46"
6066	S	67g	2.9°	Med	.600"	267	7.0	28	4.0"	.350"	46"
6066	X	67g	2.8°	Med	.600"	282	7.8	30	4.0"	.350"	46"
7070	R	75g	2.2°	Med	.600"	253	6.3	26	4.0"	.335"	46"
7070	S	76g	2.2°	Med	.600"	267	7.0	28	4.0"	.335"	46"
7070	X	76g	2.2°	Med	.600"	282	7.7	30	4.0"	.335"	46"
7076	R	76g	2.1°	Med	.600"	253	6.3	26	4.0"	.350"	46"
7076	S	77g	2.1°	Med	.600"	267	7.0	28	4.0"	.350"	46"
7076	X	77g	2.1°	Med	.600"	282	7.7	30	4.0"	.350"	46"

The new Proforce V2 was a 6-time Tour winner in 2005, its first year on the professional circuit.

It's incredible – a powerful, super low-torque golf shaft straight from the Tour. The secret is a masterful design that balances torque, weight, spin and launch angle to create the most extraordinary power-to-torque ratio in golf. The result is super low-torque Tour power in a high performance Tour shaft that can power anyone's game.

The Proforce V2 shafts were designed with the same performance profile across all three weight categories for consistency in feel. The V2 is available in the three most popular weight categories and in a full range of flexes to fit most players.

NEW Proforce V2 – L: Serious performance, fun new color!



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
5050	L	55g	5.2°	High	.580"	220	4.7	22	4.0"	.335"	46"

Ladies deserve performance as well as the coolest new color scheme on the planet. The Proforce V2-L is just the shaft for those looking for true performance, consistency and quality packed into one of the most popular new shafts on Tour.

NEW Proforce V2 Junior: V2 performance for future Tour players.



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
2900	J	62g	4.9°	High	.510"	235	4.0	17	4.0"	.335"	39"

UST offers the new Proforce V2 -Junior shaft for the up and coming young player. This is a true, high performance graphite golf shaft for serious junior golfers. Young players deserve every opportunity to win, so don't sell them short with an inferior product.

NEW Frequency Filtered Putter Shaft: Feel every putt.



Model	Description	Weight	Butt O.D.	Tip O.D.	Length
599PST	Straight Tip	106g	.600"	.370"	35.75"
599PTT	Tapered Tip	106g	.600"	.355"	35.75"
599PSB	Single Bend Tip	106g	.600"	.370"	35.75"
599P2B1P	Double Bend, 1-Plane Tip	106g	.600"	.370"	35.75"
599P2B2P	Double Bend, 2-Plane Tip	106g	.600"	.370"	35.75"
599PFT	Flared Tip	106g	.600"	N/A	35.75"
599POTH	.395 OTH Tip	106g	.600"	.395"	35.75"

The Frequency Filtered™ putter shaft lets you feel every putt clearly and precisely. Using frequency feedback to amplify touch, you feel distance and direction like never before. Just as steel shafts replaced hickory almost 100 years ago, the Frequency Filtered putter shaft is destined to become the next great innovation in golf.

HTD Counter Balance Pro: Tour proven Clubmaker series



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
5160	R	59g	3.8°	High	.600"	263	6.8	25	4.0"	.335"	46"
5160	S	60g	3.7°	High	.600"	278	7.7	26	4.0"	.335"	46"
5166	R	60g	3.7°	High	.600"	263	6.8	25	4.0"	.350"	46"
5166	S	61g	3.6°	High	.600"	278	7.7	26	4.0"	.350"	46"
6190	R	71g	3.4°	Med	.600"	264	6.8	24	3.5"	.335"	46"
6190	S	71g	3.2°	Med	.600"	282	7.7	27	3.5"	.335"	46"
6190	X	72g	3.2°	Med	.600"	301	8.5	29	3.5"	.335"	46"
6196	R	72g	3.3°	Med	.600"	264	6.8	24	4.0"	.350"	46"
6196	S	72g	3.1°	Med	.600"	282	7.7	27	4.0"	.350"	46"
6196	X	73g	3.1°	Med	.600"	301	8.5	29	4.0"	.350"	46"
9502	R	77g	3.3°	Med-Low	.600"	262	7.3	28	4.0"	.335"	46"
9502	S	81g	3.3°	Med-Low	.600"	277	7.9	29	4.0"	.335"	46"
9502	X	81g	3.3°	Med-Low	.600"	289	8.4	31	4.0"	.335"	46"
9560	R	79g	3.2°	Med-Low	.600"	262	7.3	29	4.0"	.350"	46"
9560	S	81g	3.2°	Med-Low	.600"	277	7.9	30	4.0"	.350"	46"
9560	X	81g	3.2°	Med-Low	.600"	289	8.4	32	4.0"	.350"	46"

The new HTD Counter Balance Pro series is a Tour proven winner that UST is proud to offer to custom Club Builders. Proven time and time again on the PGA Tour, HTD counter-balanced shafts fit a wide variety of golfers with varying swing styles.

This new low torque CB series was originally developed with Pros in mind, but the unique performance characteristics of counter-balancing work extremely well for players at all levels, producing longer, straighter shots.

Compare the specs with other popular shafts and you will find a superior product, and a great value. Offered in 60, 70 and 80 gram versions, this new Counter Balance Pro series from UST again raises the performance bar.

HTD Constant Weight Irons: New smoked chrome finish



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
950R02-10	R	95g	2.2°	Med	.605"	343-441	9.6-11.1	37-55	2"	.370"	39.5-35.5"
950S02-10	S	95g	2.2°	Med	.610"	357-461	10.2-11.9	40-59	2"	.370"	39.5-35.5"
950X02-10	X	95g	2.0°	Med	.610"	381-484	11.2-12.6	45-63	2"	.370"	39.5-35.5"
950TR02-10	R	95g	2.2°	Med	.605"	343-441	9.6-11.1	37-55	Taper	.355"	39.5-35.5"
950TS02-10	S	95g	2.2°	Med	.610"	357-461	10.2-11.9	40-59	Taper	.355"	39.5-35.5"
950TX02-10	X	95g	2.0°	Med	.610"	381-484	11.2-12.6	45-63	Taper	.355"	39.5-35.5"

Accuracy and distance in a 95 gram iron shaft. Each HTD Constant Weight iron shaft is engineered to a specific length, the same constant weight and a specific frequency for each iron in your bag. The demanding Tour specs and Tour tolerances provide the most consistent feel and optimum performance from club to club. Incremental lengths mean all you have to do is butt trim to length.

HTD CB-65: One of the most successful shafts on Tour



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
6160	R	66g	3.3°	Med-High	.600"	264	6.8	22	3.5"	.335"	46"
6160	S	68g	3.2°	Med-High	.605"	282	7.5	24	3.5"	.335"	46"
6160	X	69g	3.1°	Med-High	.605"	299	8.5	26	3.5"	.335"	46"
6166	R	67g	3.2°	Med-High	.600"	264	6.8	22	3.5"	.350"	46"
6166	S	69g	3.1°	Med-High	.605"	282	7.5	24	3.5"	.350"	46"
6166	X	70g	3.0°	Med-High	.605"	299	8.5	26	3.5"	.350"	46"

The HTD CB-65 was the original counter-balanced design, and is one of the most successful shafts of all time on the Tour.

This version helps create optimum ball speed and launch angle for longer ball flight and carry distance. Weight distribution near the hands makes the club easier to swing, while the unique CB design encourages a "natural draw bias" . . . extremely desirable for most players.

Low Carb: Less Torque, Higher Launch, More Performance



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
4900	L	51g	4.6°	High	.610"	220	5.0	19	4.0"	.335"	46"
4900	A	51g	4.0°	High	.610"	230	5.5	20	4.0"	.335"	46"
4900	R	52g	3.7°	High	.615"	243	6.3	22	4.0"	.335"	46"
4900	S	52g	3.7°	High	.615"	261	7.1	24	4.0"	.335"	46"
4960	L	52g	4.6°	High	.610"	220	5.0	21	4.0"	.350"	46"
4960	A	52g	4.0°	High	.610"	230	5.5	21	4.0"	.350"	46"
4960	R	52g	3.6°	High	.615"	244	6.4	23	4.0"	.350"	46"
4960	S	52g	3.6°	High	.615"	262	7.2	25	4.0"	.350"	46"

With Low Carb, less is more. Using a space-age micro carbon fiber design, the new Low Carb brings feel, playability and low torque control to the super lightweight category like never before. At 52 grams and only 3.7 degrees of torque, your daily performance will include long, high launching drives and excellent feel!

IROD Driver: The power of a driver, the control of a three wood



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
7400	A	65g	2.7°	High	.605"	238	6.3	20	4.0"	.335"	46"
7400	R	65g	2.6°	High	.605"	254	7.2	22	4.0"	.335"	46"
7400	S	65g	2.6°	High	.605"	270	7.9	24	4.0"	.335"	46"
7400	X	65g	2.6°	High	.605"	286	8.6	26	4.0"	.335"	46"
7460	A	66g	2.6°	High	.605"	238	6.3	22	4.0"	.350"	46"
7460	R	66g	2.5°	High	.605"	254	7.2	23	4.0"	.350"	46"
7460	S	66g	2.5°	High	.605"	270	7.9	25	4.0"	.350"	46"
7460	X	66g	2.5°	High	.605"	286	8.6	27	4.0"	.350"	46"

The big brother of the Tour favorite IROD Hybrid, the IROD Driver shaft is a low torque power-tool. Constructed with super responsive "Interlinked Carbon" for the heart of a long-ball hitter and the soul of a scorer! The IROD Driver, like the IROD Hybrid, is the easiest to hit high performance driver shaft you'll ever swing! It's Long! And you will be too when you put IROD in your favorite driver. Designed to make every great driver even better!

IROD Hybrid: The number one hybrid on Tour – Three shafts for three distinct types of hybrid club



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
IROD HYBRID LONG IRON											
750	A	76g	2.3°	High	.595"	279	6.8	36	5.5"	.370"	41"
750	R	78g	2.3°	High	.595"	292	7.3	38	5.5"	.370"	41"
750	S	81g	2.3°	High	.600"	306	8.0	40	5.5"	.370"	41"
750	X	82g	2.1°	High	.600"	318	8.4	42	5.5"	.370"	41"
IROD HYBRID UTILITY											
780	A	78g	2.4°	Med-High	.595"	282	7.2	45	5.5"	.370"	41"
780	R	81g	2.4°	Med-High	.595"	294	7.6	46	5.5"	.370"	41"
780	S	83g	2.4°	Med-High	.600"	311	8.4	48	5.5"	.370"	41"
780	X	84g	2.2°	Med-High	.600"	321	8.8	50	5.5"	.370"	41"
IROD HYBRID FAIRWAY											
7500	A	70g	3.4°	Med-High	.605"	264	5.7	26	4"	.335"	44"
7500	R	73g	3.4°	Med-High	.610"	275	6.3	27	4"	.335"	44"
7500	S	73g	3.4°	Med-High	.610"	292	7.1	30	4"	.335"	44"
7500	X	74g	3.2°	Med-High	.610"	303	7.5	31	4"	.335"	44"
7506	A	71g	3.3°	Med-High	.605"	264	5.7	26	4"	.350"	44"
7506	R	74g	3.3°	Med-High	.610"	275	6.3	27	4"	.350"	44"
7506	S	74g	3.3°	Med-High	.610"	292	7.1	30	4"	.350"	44"
7506	X	75g	3.1°	Med-High	.610"	303	7.5	31	4"	.350"	44"

While all three models feature "Interlinked Carbon" materials for better control in the hands, each of the models were designed to handle the specific performance requirements of Long Irons, Utility Clubs, and Fairway Woods.

Hybrid Long Iron Shaft - A more flexible tip section, with lower torque, gets the ball airborne easier, yet provides the ultimate in accuracy.

Hybrid Utility Shaft - Strong, stable tip section designed to work with the hybrid clubs of today! Created to accurately control distance and complement high launching shots.

Hybrid Fairway Shaft - Designed specifically to control shot dispersion from the fairway and for those other difficult approach shots.

Competition Series: Ultimate value, ultimate performance



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
COMPETITION 65 Light - Trim to Fit and Lighter Weight equals more distance!											
3150	A/L	63g	4.9°	High	.595"	233	5.5	20	4.5"	.335"	47"
3150	R/S	66g	4.9°	Med-High	.600"	245	6.4	22	4.5"	.335"	47"
COMPETITION 75 Series - Highly durable, combination flex shaft.											
6300	A/L	80g	5.8°	Med-High	.590"	240	6.1	26	4.5"	.335"	47"
6300	R/S	86g	5.5°	Medium	.600"	260	7.0	28	4.5"	.335"	47"
630	A/L	80g	4.8°	Med-High	.590"	295	8.1	45	6.5"	.370"	42"
630	R/S	83g	4.6°	Medium	.600"	325	9.3	46	6.5"	.370"	42"
COMPETITION PRO - A lightweight, durable replacement shaft.											
3500	L	74g	5.4°	Med-High	.565"	238	5.5	23	3.5"	.335"	45"
3500	A	76g	5.2°	Med-High	.590"	251	5.7	24	3.5"	.335"	45"
3500	R	78g	4.9°	Medium	.595"	264	6.6	26	3.5"	.335"	45"
3500	S	81g	4.9°	Medium	.600"	277	7.2	26	3.5"	.335"	45"
350	L	70g	5.0°	Med-High	.565"	315	8.6	43	5.5"	.370"	40"
350	A	75g	4.6°	Med-High	.590"	329	8.7	43	5.5"	.370"	40"
350	R	75g	4.3°	Medium	.595"	342	9.3	44	5.5"	.370"	40"
350	S	78g	4.3°	Medium	.600"	355	9.7	44	5.5"	.370"	40"

Competition Series shafts are a club builder's dream. Lightweight, durable designs provide the ultimate in club building flexibility. Longer parallel sections for greater trimming options and combination flexes can be trimmed and frequency matched to fit more golfers. This Series is a proven value.

Competition 65 - Lighter weight combo design provides ultimate club building flexibility and helps maximize distance. Wood only.

Competition 75 - Light weight and very durable - great for beginners. Combination flexes allow the club builder maximum fitting flexibility. Woods and Irons.

Competition Pro - Discrete flexes in this lightweight, durable design. Excellent replacement shaft for most clubs. Woods and Irons.

Proforce Lady Irons and Woods: In a variety of new colors!

PINK GRAPEFRUIT



TANGERINE



LIME



LEMON



ELECTRIC BLUE



CHAMPAGNE



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
PROFORCE LADY IRONS - CHAMPAGNE ONLY											
785	L	66g	4.8°	Med	.570"	314	7.8	38	4.75"	.370"	39"
PROFORCE LADY WOODS											
7850	L	66g	3.6°	Med	.580"	252	5.8	23	4"	.335"	44"

Lightweight graphite engineered for women golfers. Stable tip and low torque provide the same great playing characteristics of a Proforce. New citrus shock colors are now available in addition to the original Champagne and Electric Blue. Proforce Lady irons are available only in Champagne.

Proforce Rv2 Gold - Tour Proven Iron Series



Model	Flex	Weight	Torque	Launch	Butt O.D.	Butt Stiffness	Mid Stiffness	Tip Stiffness	Tip Parallel	Tip O.D.	Length
PROFORCE Rv2 75 GOLD											
642	A	79g	3.3°	Med-High	.595"	315	8.0	40	5.5"	.370"	40"
642	R	81g	3.2°	Med-High	.595"	330	8.6	41	5.5"	.370"	40"
642	S	83g	3.2°	Med-High	.600"	345	9.2	42	5.5"	.370"	40"
642	X	83g	3.2°	Med-High	.600"	368	10.1	47	5.5"	.370"	40"
PROFORCE Rv2 95 GOLD											
955	R	94g	2.9°	Med	.600"	332	9.4	39	5.5"	.370"	40"
955	S	95g	2.9°	Med	.600"	344	9.8	41	5.5"	.370"	40"
955	X	96g	2.9°	Med	.600"	357	10.3	43	5.5"	.370"	40"
PROFORCE Rv2 115 GOLD											
454	R	111g	2.5°	Low-Med	.600"	338	9.4	37	5.5"	.370"	40"
454	S	114g	2.5°	Low-Med	.600"	350	9.9	40	5.5"	.370"	40"
454	X	115g	2.5°	Low-Med	.600"	362	10.4	41	5.5"	.370"	40"

Taper available on request at \$2.50 per shaft

The Tour tested Proforce GOLD Iron shaft line is designed for improved balance and control. Players now have a choice of weights and flexes in these 3 models. Available in matching Smoked Mirror and Black paint, with the classic Proforce GOLD graphics. Available in .355" taper tip upon request. Proforce Rv2-75 - for the golfer looking for the higher launch and added distance of high performance, lightweight graphite shafts. Proforce Rv2-95 - for better players looking for better performance and playability than lightweight steel. Extra distance compared to standard steel and improved control compared to lightweight steel. Proforce Rv2-115 - for players looking for the feel, balance and control of a tour weighted model. Strong tip section and heavier weight provides great controlled ball flight.

Tip Trimming Instructions

The tip trimming information below is to be used for preparation of the shaft before assembly. Following the tip trimming procedure, assemble the shaft into the head. Then butt trim the shaft to the desired playing length.

Wood Shafts Parallel Tip Models				
Model	Driver	3W	5W	7W
2900, 3150L, 3150R, 3500 4900, 4960, 5050, 5056, 5160, 5166, 6000, 6060, 6066, 6160, 6166, 6190, 6196, 6300R, 6300L, 6850, 7070, 7076, 7400, 7460, 7550, 7560, 7850, 7860, 9502, 9560	0"	1"	2"	2"
3150A, 3150S, 6300S, 6300A	1"	2"	3"	3"
7500, 7506, 7950, 7960	N/A	0"	1"	2"

Iron Shafts Parallel Tip Models										
Model	1 Iron	2 Iron	3 Iron	4 Iron	5 Iron	6 Iron	7 Iron	8 Iron	9 Iron	Wedge
350, 454, 630R, 630L, 642, 750, 955	0"	1/2"	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	4"
630S, 630A	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	4 1/2"	5"	5"
785L	N/A	N/A	0"	1/2"	1"	1 1/2"	2"	2 1/2"	3"	3"
950	BUTT TRIM ONLY... NO TIP TRIM REQUIRED									

Utility Shafts Parallel Tip Models					
Model	> 40.5"	40.25" - 39.75"	39.5" - 39.0"	38.75" - 38.25"	38" - 37.75"
780	1/2"	1"	1 1/2"	2"	2 1/2"